

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 842 639 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
25.02.2004 Bulletin 2004/09

(51) Int Cl.7: **A61B 17/17, A61B 17/16,
A61B 17/56**

(21) Application number: **97308809.9**

(22) Date of filing: **03.11.1997**

(54) **Machining assembly for preparing the medullary cavity of a femur in hip arthroplasty**

Bearbeitungsanordnung zur Vorbereitung des Knochenkanals eines Femurs für künstliche Bildung
des Hüftgelenks

Ensemble d'usinage pour préparation de la cavité médullaire fémorale dans l'arthroplastie de la
hanche

(84) Designated Contracting States:
**AT BE CH DE DK ES FI FR GB GR IE IT LI LU NL
PT SE**

(30) Priority: **13.11.1996 US 749279**

(43) Date of publication of application:
20.05.1998 Bulletin 1998/21

(73) Proprietors:
• **Stryker Technologies Corporation**
Kalamazoo, MI 40992 (US)
• **Noble, Philip Christopher**
Houston, Texas 77030 (US)

(72) Inventors:
• **Noble, Philip C.**
Houston, Texas 77030 (US)

• **Hammer, Michael A.**
Pine Brook, New Jersey 07058 (US)
• **Eckrote, Richard G.**
Lincoln Park, New Jersey 07035 (US)
• **Schulzki, Michael**
Boonton, New Jersey 07005 (US)
• **Axelson, Stuart**
Succasunna, New Jersey 07876 (US)

(74) Representative: **Bridge-Butler, Alan James et al**
G.F. Redfern & Co.,
7 Staple Inn,
Holborn
London WC1V 7QF (GB)

(56) References cited:
WO-A-94/12124 WO-A-94/27507
GB-A- 2 250 441 US-A- 5 169 401
US-A- 5 169 402

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

EP 0 842 639 B1

Description

BACKGROUND OF INVENTION:

5 [0001] The present invention relates to a broach for preparing a medullary cavity for receiving a stem component of a femoral prosthesis, specifically an improved machining assembly for preparing a medullary cavity that allows for the implantation of a femoral prosthesis that is neutrally aligned within the prepared medullary cavity for improved fixation therein, thereby minimizing any subsequent loosening and pain commonly associated with mis-aligned prostheses.

10 [0002] It is widely known that the success of cementless hip replacement depends on correct sizing and placement of prosthesis within the medullary cavity of the femur. In cases that fail due to aseptic loosening, a common observation is that the implant is not large enough to achieve support through filling the implant site and thereby achieving contact with the cortical surfaces of the femur. Typically, these undersized prostheses are mis-aligned and have been placed in some degree of varus inclination with respect to the medullary axis of the femur. Consequently, the implant only achieves contact with the cortex of the femur medially, immediately below the surface of the proximal femoral osteotomy, and laterally, adjacent to the distal tip of the prosthetic stem. However, contact is not present in other areas, including 15 the anterior and posterior cortices, the medial cortex beneath the lesser trochanter, or the lateral cortex above the distal tip of the implant. Contact in these areas is necessary to rigidly fix the prosthesis and to prevent excessive relative motion at the implant/bone interface which would lead, ultimately, to pain and loosening.

20 [0003] In practice, prostheses that are implanted in the femur are undersized because the opening formed by the surgeon does not extend far enough laterally within the proximal femur to allow the prosthesis to be aligned with the longitudinal axis of the canal. This occurs because the medullary axis passes through the superior surface of the femur in the vicinity of the medial edge of the greater trochanter, close to the posterior cortex of the femoral neck, in an area of strong bone which is difficult to machine using conventional instruments, including broaches, rasps, and reamers. As the bone adjacent to this area is relatively soft, conventional machining instruments tend to be deflected away from 25 the hard bone and enter the medullary canal at a site that is located more anteriorly and medially. As subsequent instruments enlarge the initial point of entry, bone is progressively removed from the anterior and medial walls of the cavity, leading to the development of a mis-aligned implantation site.

30 [0004] If a broach or rasp is placed into a femoral canal through an entry hole that is not aligned with the medullary axis, the broaching or rasping instrument will become wedged in the canal because the teeth present on the devices are generally incapable of effectively removing areas of hard bone which block their advancement. Removal of this bone, generally, can only be effected by rotating machine tools, such as flexible or rigid reamers or, possibly, bone chisels. Thus, in conventional hip replacement, preparation of a neutrally-aligned implantation cavity depends critically upon the initial entry point of instruments into the femur and the use of adjunctive instruments to machine away the areas of hard bone that block the motion of the broach as it seeks to achieve neutral alignment within the canal.

35 [0005] The anatomic variability of the proximal femur also contributes to mis-alignment and undersizing of femoral prostheses. The medullary axis passes through the superior surface of the femur at a point that varies by +/- 5 mm medial-laterally and anterior-posteriorly, the precise location depending upon the shape of the metaphysis and the orientation of the femoral neck with respect to the rest of the femur. For this reason, it is difficult to determine intraoperatively whether instruments placed in the femoral canal are correctly aligned and whether the entry point for instruments designed to machine the femur is situated sufficiently laterally and posteriorly to allow development of a neutrally aligned implantation site.

40 [0006] The conventional approach to minimizing the difficulties in preparing the femur in the presence of areas of hard bone has been to insert a reaming instrument, typically a long, conical reamer or medullary drill, into the medullary cavity and to assume that the instrument would be co-axial with the medullary cavity during its insertion, in effect forcing the proximal part of the instrument to cut into the greater trochanter to an extent necessary to provide correct alignment 45 of the prepared cavity. In practice, this approach has not been entirely successful because of the following factors:

(1) The bone within the trochanter is generally very hard, greasy, and often covered with a considerable quantity of soft tissue which tend to impair the cutting action of conventional drilling and reaming instruments.

50 (2) This approach assumes that the instrument will be aligned with the medullary cavity without enlarging or cutting the bone distally, thereby distorting the cavity itself. In practice, the use of long drills and instruments that are not smooth-tipped can lead to mis-alignment because the instrument cuts bone both proximally and distally.

(3) The entire approach of using the intramedullary cavity to guide the alignment of instruments assumes that the diaphyseal and metaphyseal segments of the femur coincide. In practice, however, there is a deviation of up to 55 two degrees between the axis of the metaphysis and the diaphysis of the medullary cavity. Consequently, the path machined by the distally-guided instrument only gives a rough indication of where a neutrally-positioned instrument should lie within the metaphysis.

(4) Aggressive reaming instruments and drills often remove a considerable segment of the greater trochanter

during their insertion. This necessitates greater exposure of the surgical site and removal of excessive bone, and may lead to increased long-term osteolysis as soft cancellous bone is exposed to wear debris generated within the joint.

[0007] There exist many devices that assist the process of shaping the femoral canal to match the contours of the femoral implant; however, the successful function of each of these devices is predicated on the assumption that some instrument has been inserted into the medullary canal in a neutral position. Such an instrument is then used as a platform for locating reamer guides of a variety of designs. Such instruments have been available commercially and are primarily used to facilitate reaming of the medial bone within the femur, which is often very strong and may prevent the use of a correctly sized prosthesis. Exemplary instruments are manufactured by Biomet, Inc. (Warsaw, Indiana) and are also disclosed in U.S. Patent Nos. 4,809,689 (Anaplotis), 4,777,942 (Frey, et al.), and 4,738,256 (Freeman et al.).

[0008] Additional instrument designs are available for use with modular prostheses comprising interchangeable anterior and posterior elements which are mounted on the central stem of the prosthesis. The Richards Medical Company (Memphis, Tennessee) manufactures a system consisting of a plurality of modular reaming guides that utilize a rail attached to a stent placed in the medullary canal. The function of the rail is to guide the position of the reamer used to machine both the anterior and posterior surfaces of the femur to optimize the fit of this prosthesis within the femur.

[0009] Another design is disclosed in U.S. Patent No. 5,169,402 (Elloy) and comprises a broach having two separate parts that connect on an articulating handle to form a solid, uniform piece. The smaller segment of the original broach consists of the medial part of the broach, extending down from the upper face of the osteotomy level. This segment is spring-loaded so that as the surgeon drives the broach into the femur, the medial segment gets caught at some point within the medial cortex. Consequently, as the surgeon advances the body of the instrument further down the femur, the medial segment slides along a track present in the body and remains in a position protruding from the bone. The motion of the segment is constrained by a spring, so that once the rest of the broach has become seated in the bone, the surgeon may drive the medial segment alone into place within the femur, thereby completing the machining operation to form the implantation cavity. WO 9427507 discloses a typical machining assembly for removing the soft medial or calcar region of the medullary cavity.

[0010] According to the present invention a machining assembly suitable for use in preparing a bone cavity for subsequent implantation of a prosthesis, said assembly comprises a femoral broach designed for placement within a bone cavity to prepare said bone cavity for implantation of a prosthesis, said femoral broach comprising a superior end, and a lateral face on which is a lateral recess extending downward from said superior end, said recess configured to avoid the bone of the greater trochanter; a guide secured to said femoral broach and configured to receive a second bone cutting instrument; and a second bone cutting instrument carried within said guide, said second bone cutting instrument being adapted to enter said lateral recess to remove additional bony material from the lateral side of the cavity after placement of said femoral broach within said cavity and prior to implantation of said prosthesis within said prepared bone cavity.

[0011] The invention also includes a femoral broach for use in the machining assembly set forth above, which is designed for placement with a bone cavity to prepare said cavity for implantation of a prosthesis, said femoral broach having a superior end and a lateral face on which is a lateral recess extending downward from said superior end.

BRIEF DESCRIPTION OF THE DRAWINGS

[0012] The objects, advantages, and features of the invention will become more apparent by reference to the drawings which are appended hereto, wherein like numerals indicate like parts and wherein an illustrated embodiment of the invention is shown, in which:

Fig. 1 is a posterior view of a neutrally aligned prosthesis implanted within a femur.

Fig. 2 is a posterior view of a mis-aligned prosthesis implanted within a femur.

Fig. 3 is an anterior view of a left component of the inventive broach.

Fig. 3A is an anterior view of a full broach used to construct the partial broach.

Fig. 3B is a lateral view of the full broach illustrated in Fig. 3A.

Fig. 4 is medial view of the inventive broach.

Fig. 5 is a top plan view of the inventive broach.

Fig. 6 is an anterior view of a left component of the inventive broach illustrating the positioning of the preferred cutting teeth.

Fig. 6A is an anterior view of the left component of another embodiment of the inventive broach illustrating the broach implanted within the medullary cavity of a femur.

Fig. 7 is an anterior view of the inventive machining assembly implanted within the medullary cavity of a femur.

Fig. 8 is an anterior view of the assembled machining assembly, including a cutting instrument and broach.
 Figs. 9-11 are front, back, and side views, respectively, of the guide component of the machining assembly.
 Fig. 12 is a medial view of the machining assembly (without the broach and second cutting instrument).
 Fig. 13 is a cross-section view of the machining assembly taken along lines 13-13 of Fig. 12 illustrating the preferred means for securing the guide to the mounting block.
 Fig. 14 is a bottom plan view of the machining assembly (without the broach and second cutting instrument).
 Fig. 15 is a lateral view of the machining assembly (without the broach and second cutting instrument).
 Fig. 16 is an enlarged view of the spring plunger.
 Fig. 17 is an enlarged view of the locking screw for securing the guide to the mounting block.
 Fig. 18 is a longitudinal cross section view of the mounting block illustrating the various channels and bores.
 Fig. 19 is a side view of the machining assembly (without the broach and cutting instrument).
 Fig. 20 is a cross section view of the machining assembly taken along lines 20-20 of Fig. 19 illustrating the preferred means for securing the broach to the mounting block.
 Fig. 21 is a side view of the machining assembly.
 Fig. 22 is a cross-section view of the machining assembly taken along lines 22-22 of Fig. 21, wherein the locking assembly is shown in the home or retracted position to secure the broach within the mounting block.
 Fig. 23 is the cross-section view of the machining assembly as illustrated in Fig. 22, wherein the locking assembly is shown in the open position to allow insertion of the broach within the mounting block.
 Figs. 24A-24B are side views of the preferred second cutting instrument component of the machining assembly.
 Fig. 25A is an enlarged view of the distal tip of the second cutting instrument illustrated in Figs. 24A-24B.
 Figs. 25B is a bottom plan view of the second cutting instrument illustrated in Fig. 25B.
 Figs. 25C is a cross-section view of the distal tip taken along lines 25C-25C of Fig. 25B.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS:

I. Partial Broach Design

[0013] The present invention is directed to an improved broach design and machining assembly for preparing the medullary cavity of a femur for subsequent implantation of a femoral prosthesis in hip arthroplasty. After the medullary cavity is prepared using the inventive broach, a femoral stem component of a hip prosthesis may then be implanted within the cavity, wherein the longitudinal axis of the stem is in neutral alignment with the medullary axis of the femur, resulting in improved rigid fixation of the stem, thereby minimizing the possibility of future loosening of the implant and pain associated with such loosening. The phrase "neutral alignment" as used herein refers to the substantial coincidence of longitudinal axes, specifically the medullary axis of the femur and the longitudinal axis of the broach or femoral prosthesis, as discussed in further detail below.

[0014] When preparing the implantation site within the medullary cavity, it is desirable that the site be configured such that upon implantation of the femoral prosthesis, full contact is achieved between the outer surface of the stem and the surface of the cavity. As illustrated in Fig. 1, such contact is achieved when the stem (S) is placed in neutral alignment within the medullary cavity (C) (i.e. the longitudinal axis (Y^1) of the stem (S) and the medullary axis (Y) of the femur (F) substantially coincide). Fig. 2 illustrates an undesirable implantation due to inaccurate broaching of the cavity where only partial contact is achieved between the stem (S) and the medullary cavity (C) (as shown in circled areas x and y). In addition, a gap is present between the stem (S) and the lateral cortex (4) in the region (z). Consequently, such broaching has resulted in misalignment of the stem (S) wherein the longitudinal axis (Y^1) of the stem (S) is placed in some degree of varus alignment (5) with respect to the medullary axis (Y) of the femur.

[0015] As discussed above, a problem that often occurs during conventional broaching/rasping is that the cutting instrument is deflected away from the hard bone of the greater trochanter (1), especially in the vicinity of the posterior margin of its medial wall (3), where the bone is generally very difficult to machine with conventional instruments, thereby altering the path of the instrument towards the softer adjacent bone at a site that is located more anteriorly and medially. As subsequent cutting instruments enlarge the initial point of entry, the bone is progressively removed from the anterior and medial walls of the cavity, leading to the development of a mis-aligned implantation site.

[0016] The present invention is directed to a broach design and machining assembly for preparing the implantation site within the medullary cavity to allow for neutral alignment of a subsequently implanted femoral stem prosthesis, namely by employing a design that allows the broach to avoid the greater trochanter during initial broaching and preparation of the implantation site. Referring now to Figs. 3-6A, the present invention comprises a partial broach (10) having a longitudinal axis (X), anterior (A), posterior (P), medial (M), and lateral (L) faces, a plurality of teeth (17) positioned on at least one the faces (shown in Figs. 6, 6A, and 7), and a lateral recess (13) positioned on the proximal segment (11) (i.e. about upper one-third) of the broach. While the smallest recess should occupy the posterior/lateral corner of the broach (not shown) to avoid the bulky region of the greater trochanter, the most preferred embodiment

comprises a lateral recess (13) that extends from the anterior face (A) to the posterior face (P), as shown in the figures. It should be further noted that while the description of the invention and the related figures are directed to a left femoral broach, the present invention may also be designed for a right broach, which is merely a mirror image of the left broach described and illustrated herein.

[0017] Figs. 3-6A illustrate a preferred configuration of the recess (13); however, alternative configurations of the recess may be employed, provided that each are of sufficient depth and proper placement to allow the broach to avoid the desired bony area, typically the greater trochanteric region of the femur. Figs. 3 and 5, for example, illustrate a preferred lateral recess design which comprises, in a series, a substantially flat back portion (14) (extending from about point a of the superior end (12)) and a base portion comprising a concavity (15a) extending from the back portion and terminating at a distal edge (16). The base portion further includes a chamfer (15b) extending from the distal edge (16) to about point b and preferably positioned at an angle (6) of about 30 to about 60 degrees, most preferably about 45 degrees, relative to the longitudinal axis (X) of the broach. The chamfered edge (15b) of the recess is a preferred design feature that allows the broach (10) to avoid impingement against lateral bone beneath the greater trochanter, thereby minimizing the chance of a fracture upon extraction of the broach from the femur.

[0018] As illustrated in Figs. 6-6A, the broach comprises a plurality of cutting teeth (17) positioned on at least the medial face (M), but most preferably on all four faces of the broach (10). The configuration of the cutting teeth may be the same on all of the faces; however, the most preferred types and arrangement of cutting teeth are those shown in Fig. 6 as well as those described and illustrated in co-pending application Serial No. 08/594,892. While the preferred embodiment of the broach described in Serial No. 08/594,892 comprises a plurality of aggressively cutting diamond-shaped teeth on the lateral face, the presence of a lateral recess on the partial broach minimizes the need for aggressive cutting of lateral bone.

[0019] In the preferred embodiment, the partial broach is prepared from a "full" broach (i.e. one not having a lateral recess), as illustrated in Figs. 3A and 3B, whereby the recess portion is cut out of the full broach. Preferably, the material is removed from the proximal lateral face of the broach such that the "length" of the recess (l_1) (see Figs. 3 and 3A) is from about (25.4 mm) (1.0 inch) to about (30.5 mm) (1.2 inches), most preferably about (28.6 mm) (1.125 inches). Moreover, the preferred depth (d) of the recess, as illustrated in Fig. 3, is from about (20.3 mm) (0.80 inches) to about (33 mm) (1.3 inches), with the preferred radius of the concavity ranging from about (8.9 mm) (0.35 inches) to about (17.8 mm) (0.70 inches), most preferably from about (12.7 mm) (0.500) to about (15.9 mm) (0.625 inches). Table 1 lists the preferred depths (d) of the recess and size of the concavity radius for particular broach sizes.

[0020] The broach may be supplied in a range of different sizes to meet different surgical requirements. Table 2 lists preferred widths (w) and longitudinal lengths (l) for particular broach sizes. The width (w) values are obtained from a full broach (Figs 3B) measured from the anterior face to the posterior face. Moreover, in the coronal plane, the neck (21) of the broach is positioned at an angle (7) relative to the broach's longitudinal axis (X) of about 36 degrees, as illustrated in Fig. 3. Preferably, the overall configuration of the broach is the same as the configuration of the femoral prosthesis employed (except for the lateral recess). The figures illustrate an asymmetric design wherein the broach possesses a slight posterior bow, as best illustrated in Fig. 4.

TABLE 1

Broach size	Depth (d)		Radius	
	mm	(inches)	mm	(inches)
No. 2	22.8	(0.897)	12.7	(0.500)
No. 3	25.6	(1.010)	12.7	(0.500)
No. 4	28.4	(1.120)	15.9	(0.625)
No. 5	31.0	(1.221)	12.7	(0.500)
No. 6	32.8	(1.290)	15.9	(0.625)
No. 7	32.6	(1.283)	15.9	(0.625)
No. 8	32.4	(1.277)	15.9	(0.625)

TABLE 2

Broach size	Length (l_1)		Width (w)	
	mm	(inches)	mm	(inches)
No. 2	119.4	4.699	17.9	0.704
No. 3	123.5	4.863	19.2	0.757

TABLE 2 (continued)

Broach size	Length (l ₁)		Width (w)	
	mm	(Inches)	mm	(Inches)
No. 4	127.5	5.019	21.0	0.827
No. 5	131.2	5.164	22.3	0.878
No. 6	137.0	5.395	24.1	0.949
No. 7	135.8	5.347	25.5	1.002
No. 8	143.9	5.667	27.1	1.068

II. Surgical Method of Using the Partial Broach:

[0021] The broach (10) is generally used in conjunction with a drill or awl (not shown) which is utilized to form an entry hole in the superior cortex of the femoral neck, preferably in the vicinity of the exit point (3) of the medullary axis (Y) (see Figs. 1 and 2). Once a hole has been made that is large enough to accommodate the distal tip (22) of the broach, a detachable handle (not shown) is rigidly attached to the superior surface of the broach which is then driven into the femur (F) with a mallet or similar instrument. As the broach is advanced down the femur, it will generally rotate until contact is achieved with the medial cortex proximally and the lateral femoral cortex just below the level of the lesser trochanter (2). If necessary, a succession of broaches or rasps of increasing size may be passed down the femur until a rigid fit is achieved at the appropriate position within the femur to allow optimal reconstruction of the femoral head center. At this point, an intimate fit will be achieved between the broach and the medullary cavity, and consequently the longitudinal axis (X) of the broach (10) and the medullary axis (Y) will substantially coincide (i.e. be in neutral alignment).

[0022] Once the femur has been prepared using the broach, a second finishing broach may be implanted in the femur to enlarge the implantation site to its final shape. Since generally the finishing broach is minimally larger than the inventive broach, with the exception of the recessed area, all of the energy delivered to the finishing broach can be utilized solely in removing bone in the medial aspect of the greater trochanter, which was initially avoided by the partial broach. The finishing broaches with cutting teeth of conventional diamond-shaped configuration can be readily implanted in a neutral orientation, provided that the implantation cavity has been initially prepared with the inventive broach.

III. Machining Assembly:

[0023] As illustrated in Figs. 7-25C, the broach is used in combination with a machining device comprising a guide (200) configured to receive a second cutting instrument (208), the latter instrument being designed to machine additional bone initially avoided by the broach. Fig. 8 illustrates the preferred machine assembly comprising, in combination, the inventive broach (10) and a machining device comprising a mounting block (101), a guide (200), and a second cutting instrument (208). Alternatively, the machining assembly could include other types of cutting instruments in instead of the inventive partial broach for insertion within a bone cavity if desired for a particular procedure, including but not limited to, a full broach (e.g. Fig. 3A), rasp, reamer, and the like. Furthermore, other means for securing the guide to the broach, other than a separate mounting block (101) as illustrated and described herein, for example, are within the scope of the present invention. A more detailed description of the specific components of the preferred embodiments of the machining assembly, however, will be discussed further below.

[0024] Once the broach has been advanced to the desired position within the medullary canal, a machining device including a guide (200) and a second cutting instrument (208) may be attached to the broach to remove additional bone initially avoided by the broach, as shown in Fig. 8, for example. The shape of the lateral recess (13) of the broach allows the second cutting instrument (208) to be advanced into the cavity (C) to machine away areas of the medial aspect of the greater trochanter (1) to enable insertion of a second broach, such as a finishing broach (not shown), or femoral prosthesis of similar shape as the inventive broach (except for the presence of a lateral recess). Once the second cutting instrument (208) has been advanced within the recess so that all bone is removed, the machining assembly including the broach are removed from the femur. At this point a prosthesis, for example, of suitable shape designed to engage the machined cavity may be implanted in the femur (see Fig. 1, for example). Alternatively, a finishing broach with a shape similar to the inventive broach and the implantation site may be introduced into the femur to generate the final shape of the cavity and to remove discontinuities present between the areas of the femur that were in contact with the inventive broach and machined by the second cutting instrument (208).

[0025] The remaining discussion will be directed to the specific components of the preferred machining assembly (100). Referring now to Figs. 9-18, the machining assembly (100) comprises a guide (200) for receiving and directing

the movement of the cutting instrument (208), more preferably including a means for securing the guide to a mounting block (101), and most preferably a means for allowing slidable engagement of the guide within the block (101) to permit multiple cutting positions relative to the block (101). Alternatively, the guide may be permanently attached to the mounting block or even directly to the broach by some other means of attachment. Preferably, the guide (200) comprises a body (201) having an outer surface (201 a) and an inner passage (203) communicating therethrough for receiving a second cutting instrument (208).

[0026] The second cutting instrument (208) preferably includes a means for limiting the distance it may travel through the guide, preferably a collar (208a) affixed to the upper end of the instrument and which rests on the upper edge of the guide, for example as shown in Fig. 8. In the preferred embodiment, the cutting instrument is a cylindrical reamer which passes through a cylindrically-shaped guide, as illustrated in the figures; however, other means of machining bone are contemplated to be within the scope of the present invention, including, but not limited to, a hollow drill, a bone punch, or a chisel configured to match the shape of the recess.

[0027] A preferred second cutting instrument (208) is a 90-degree point cutter as illustrated in Figs. 24A-24B and 25A-25C. Here, the cutting instrument (208) comprises a body portion having preferably six flutes (211) and a distal tip (212) comprising a total of six cutting edges - two cutting edges (212a) converging into a point at a 90-degree angle (8) and four cutting edges (212b) terminating into a flat plane (212c) perpendicular to the longitudinal axis (Z) of the cutting instrument (208).

[0028] The guide preferably includes an arm (202) which may be permanently secured to the mounting block; however, in the most preferred embodiment, the guide arm (202) is slidably engaged within a complementary transverse chamber (205) passing through the block (Fig. 18). In this embodiment, the arm may be adjusted to different positions laterally for a desired cutting area, as discussed above. The machining assembly includes a means for securing the arm (202) within the chamber (205), preferably a locking screw (206) having a head (206a) and a lower body (206b) engaged within a complementary longitudinal bore (207) positioned on the superior end (102) of the block and in the communication with the transverse chamber (205). When the screw head (206a) is turned in one direction, the lower body (206b) of the screw moves downward to contact the guide arm (202) to preclude any further sliding movement of the guide arm within the chamber (205). When the screw head is turned in the opposite direction, the lower body is retracted to release the arm (202), thereby permitting slidable movement of the guide arm within the chamber. Fig. 17 illustrates an enlarged view of a locking screw design, wherein the lower body (206b) is further divided into four segments: a narrow segment (206c) subjacent the screw head (206a); a wide segment (206d) subjacent the narrow segment; an elongated segment (206e) subjacent the wide segment (206d); and a distal tip (209) having a diameter larger than the superior elongated segment (206e). Furthermore, to prevent the locking screw (206) from being disassembled from the mounting block (101) and possibly lost, a grooved pin (104) is employed which is contained within a complementary chamber (104a) communicating through the mounting block (101) adjacent the locking screw (206), as shown in Figs. 13, 18, and 19, for example. Upon retraction of the locking screw (206), the upper edge (209a) of the lower tip (209) of the screw contacts the grooved pin (104) to prevent further upward movement and subsequent removal of the locking screw from the mounting block (101).

[0029] Referring specifically to Figs. 9, 13, 16, and 18, the guide arm (202) preferably includes a means for adjusting the guide at multiple positions relative to the mounting block, most preferably a plurality of indentations (204) positioned on the upper surface of the guide arm, and a spring biased plunger (300) engaged within a complementary longitudinal bore (302) parallel to the locking screw (206) and perpendicular to the transverse chamber (205). The plunger (300) includes a spring loaded lower resilient tip (301) which protrudes into the transverse chamber (205), such that when an indentation (204) is positioned directly beneath the plunger, the lower tip (301) engages the indentation (204). The indentations are spaced apart from each other at desired intervals corresponding to different size broaches that may be employed during the surgical procedure. For example, the guide (200) illustrated in Figs. 9-11 comprises two indentations spaced apart to correspond to two different broach sizes (i.e. No. 4 and No. 5 broaches). Preferably, the sizes are engraved on the guide arm (202) and can be viewed by the surgeon through an opening (105) in the block. Finally, while guide arms of different configurations may be employed, the preferred configuration is one having at least three flat sides that correspond to a transverse chamber (205) having at least three corresponding sides to prevent rotational movement of the arm about a transverse axis (210) defined within the chamber (205). The most preferred embodiment as illustrated in the figures comprises six sides (202b) arranged as illustrated in Figs. 9-11 for greater engagement and wear.

[0030] Referring now to Figs. 12-15 and 18-23, the inventive machining assembly (100) further includes a means for securing a broach to the mounting block (101). While other conventional locking means known by those of ordinary skill in the art may be employed, the figures illustrate a preferred locking mechanism which includes a bore (400) present in the inferior end (103) of the block and configured for receiving a boss or trunion (18) positioned on the superior end (12) of the broach. Also carried on the mounting block (101) is a locking pin assembly comprising a spring biased push pin (401) engaged within a first complementary transverse chamber (402) positioned above the bore (400), a locking pin (403) engaged within a second complementary transverse chamber (404) parallel to the first cham-

ber (402) and in communication with the bore (400), wherein the second chamber (404) is positioned between the bore (400) and the first chamber (401), and a connecting piece (405) securing one end of the locking pin (403) to an end of the push pin (401). Preferably, the push pin (401) is housed within a helical spring (401a) having a sufficiently high compression to ensure stability of the locking system. As illustrated in Figs. 21-23, when the spring pin (401) is actuated (i.e. pushed in the direction of the arrow), the locking pin (403) is disengaged from its corresponding transverse chamber (404) to allow entry of the broach's boss or trunion (18) into the bore (400) (Fig. 22). Upon subsequent release of the push pin (401), the locking pin (403) re-enters the bore (400) to lock the boss (18) therein, thereby securing the broach to the mounting block (101) (Fig. 23). Preferably, the locking pin (403) is tapered to slide into, and be received by, a corresponding notch (19) positioned on the trunion or boss (18). For additional stability, the mounting block may also include a small key member (406) (Figs. 14-15, and 18) that extends downward below the bore (400) and is configured to engage a complementary groove (20) positioned on the superior end (12) of the broach adjacent the trunion or boss (18), as illustrated in Fig. 5, for example. Engagement of the key member (406) within the groove (20) functions to prevent any rotational movement of the mounting block (101) about the longitudinal axis (X) of the broach (10).

[0031] The present invention is particularly advantageous in the preparation of a femoral medullary cavity for receipt of a femoral prosthesis whereby upon subsequent implantation of the prosthesis, the longitudinal axis of the prosthesis substantially coincides with the medullary axis, thereby achieving neutral alignment within the cavity for more rigid fixation and stability. One method of preparing the desired implantation site is to drive the partial broach into the medullary cavity as described above in Section II. Once the medullary cavity has been prepared using the partial broach, a second finishing broach that does not contain a lateral recess may then be used to enlarge the implantation site to its final shape as well as remove bone in the medial aspect of the greater trochanter. In the most preferred embodiment, however, the inventive machining assembly as described herein is employed in combination with, or in lieu of, the second finishing broach, at least with respect to removal of bone from the greater trochanteric region of the femur. Fig. 7 illustrates the machining assembly (100) implanted within the medullary cavity (C) of a femur (F). Here, once the broach is implanted into the medullary cavity at the desired location, the mounting block (101), having lateral (L¹) and medial (M¹) sides is secured to the trunion (18) by means of the locking pin assembly described above. The guide (200) is then secured within the transverse chamber (205) and placed on the lateral side (L¹) of the mounting block over the recessed area (13) of the broach (10) at a position corresponding to the desired broach size. The second cutting instrument (208) is then placed within the guide and advanced into the recessed cavity, preferably by means of a straight plunge, to machine away areas of the medial aspect of the greater trochanter to enable insertion of another broach or prosthesis of similar shape to the inventive partial broach (but without having the lateral recess). Once the second cutting instrument (208) is advanced to the base portion of the recess (i.e. the concavity (15a)), the cutting instrument (208) may be withdrawn from the recess, the guide transferred to a new position, and then the cutting instrument (208) is again advanced to the maximum possible depth (i.e. the base of the recess). This process may be repeated until all bone within the recess has been removed. Alternatively, a side cutting reamer (not shown) may be advanced through the guide and then moved along a curved track in a side-cutting manner until all bone has been removed.

[0032] For ease of explanation, the description of the design and use of the inventive machining assembly has been confined to the preferred method of use, namely in preparing the femoral medullary cavity to receive a femoral prosthesis during hip arthroplasty. As discussed above, when the machining assembly includes the inventive partial broach described herein, it possible to prepare a medullary cavity that allows for the subsequent implantation of a neutrally aligned femoral stem component. It is contemplated, however, that one of ordinary skill in the art, having the benefit of the invention's teachings and suggestions, could make any necessary modifications to the machining assembly, including the broach, for other orthopedic surgical procedures requiring the removal of bone.

[0033] The preferred materials for fabricating the components of the machining assembly, including the inventive broach, are those typically employed in orthopedic surgical instruments and implants, including, but not limited to, stainless steels and alloys of cobalt, chromium, and molybdenum. Preferred materials include 455 and 17-4 precipitated hardenable stainless steels. For optimal results, the outer surface of the second cutting instrument employed within the guide is preferably electropolished and coated with a chromium nitride or similar surface hardening compound.

[0034] The foregoing disclosure and description of the invention are illustrative and explanatory thereof, and various changes in the size, shape, and materials, as well as in the details of the illustrated construction, including, but not limited to, modifications necessary to accommodate variations in patient anatomy, may be made without departing from the scope of the claims.

Claims

1. A machining assembly suitable for use in preparing a bone cavity for subsequent implantation of a prosthesis, characterised in that said assembly comprises:

a femoral broach (10) designed for placement within a bone cavity to prepare said bone cavity (C) for implantation of a prosthesis (S), said femoral broach (10) comprising a superior end (12), and a lateral face (L) on which is a lateral recess (13) extending downward from said superior end, said recess configured to avoid the bone of the greater trochanter;

a guide (200) secured to said femoral broach (10) and configured to receive a second bone cutting instrument (208); and

a second bone cutting instrument (208) carried within said guide (200), said second bone cutting instrument (208) being adapted to enter said lateral recess (13) to remove additional bony material from the lateral side of the cavity (C) after placement of said femoral broach (10) within said cavity (C) and prior to implantation of said prosthesis within said prepared bone cavity (C).

2. A machining assembly as claimed in claim 1 which includes a mounting block (101) secured to said femoral broach (10).

3. A machining assembly as claimed in claim 2 in which said guide (200) comprises a body (201) having an outer surface (201A) and an inner passage (203) communicating therethrough to accommodate said second bone cutting instrument (208), and a guide arm (202) integral with said outer surface of said body (201) and secured to a mounting block (101).

4. A machining assembly as claimed in claim 3 further including a means for securing said guide to said mounting block (101) said securing means including an inner transverse chamber (205) contained within said mounting block (101) and communicating therethrough, wherein said chamber is configured for slidable engagement of said guide arm (202) therein.

5. A machining assembly as claimed in claim 3 or claim 4, wherein said means for securing said guide to said mounting block further includes a locking screw (206) having a head (206a) and a lower body (206b) engaged within a first complementary longitudinal bore (207) positioned on the superior end (102) of the block, said bore in communication with said transverse chamber (205);
whereby when said locking screw is turned in one direction, the lower body of the screw achieves contact with said guide arm to preclude sliding movement of said arm within the chamber, and when said screw is turned in an opposite direction, said lower body of the screw is retracted to release said arm, thereby permitting slidable movement of the guide arm within the transverse chamber.

6. A machining assembly as claimed in claim 4 or claim 5, wherein said guide arm (202) and said transverse chamber (205) are configured to prevent rotational movement of said guide arm about a transverse axis (210) defined within said chamber.

7. A machining assembly as claimed in claim 5 or claim 6, wherein said guide further includes a means for adjusting the guide at multiple positions relative to said mounting block, said adjusting means including an indentation (204) positioned on said guide arm and a spring biased plunger (300) engaged in a second complementary bore (302) parallel with said locking screw (206) and perpendicular to said transverse chamber (205), said plunger having a lower tip (301) protruding into said chamber; whereby when said indentation is positioned beneath said plunger, the lower tip is engaged within said indentation.

8. A machining assembly as claimed in any one of preceding claims 2 to 7 including means for securing said femoral broach (10) to said mounting block (101) said securing means including:

(a) a first bore (400) configured to receive a boss (18) positioned on said superior end (12) of said femoral broach (10); and

(b) a locking pin assembly comprising a spring biased pin (401) engaged within a first complementary transverse chamber (402) positioned above said first bore (400), a locking pin (403) engaged within a second complementary transverse chamber (404) parallel to said first transverse chamber and positioned between said first chamber and first bore, said second transverse chamber being in communication with said first bore; and a means for connecting said locking pin to said spring biased pin;

whereby when said spring biased pin is actuated, said locking pin is disengaged from said second transverse

chamber to allow entry of said boss into said first bore, and whereby upon subsequent release of said spring biased pin, said locking pin is engaged within said first bore to lock said boss of said femoral broach (10) therein.

9. A machining assembly as claimed in claim 8, wherein said locking pin (403) has a tapered end.
10. A machining assembly as claimed in claim 8 or claim 9, wherein said boss (18) includes a notch (19) configured to receive said locking pin (403) for rigid fixation of said femoral broach (10) within said first bore (400).
11. A machining assembly as claimed in any one of preceding claims 8, 9 or 10, wherein the inferior end (103) of said mounting block (101) has a key member (406) extending downward below said first bore (400) and configured to engage a complementary groove (20) located on said superior end (12) of said femoral broach (10) adjacent said boss; whereby when said boss is rigidly engaged with said first bore of said mounting block, said key member is engaged within said groove to preclude rotational movement of said mounting block about the longitudinal axis (X) of said femoral broach (10).
12. A machining assembly as claimed in claim 1 in which said femoral broach (10) comprises a longitudinal axis (X); anterior (A), posterior (P), medial (M), and lateral (L) faces; a plurality of cutting teeth (17) positioned on at least one of said faces; a proximal segment including said faces and having a superior end (12) and a recess (13) positioned on said lateral face of said proximal segment and extending downward from said superior end, said recess configured to avoid the greater trochanteric bone upon implantation of said broach within said cavity.
13. A machining assembly as claimed in claim 12, wherein said recess (13) extends from said posterior (P) face to said anterior (A) face.
14. A machining assembly as claimed in claim 13, wherein said recess (13) includes a back portion (14) and a base portion (15).
15. A machining assembly as claimed in claim 14, wherein said base portion comprises a concavity (15a) having a distal edge (16).
16. A machining assembly as claimed in claim 15, wherein said recess further includes a chamfer (15b) extending downward from said distal edge (16) of said concavity (15a).

Patentansprüche

1. Bearbeitungszusammenstellung, die zur Verwendung bei der Vorbereitung eines Knochenhohlraums zur nachfolgenden Implantation einer Prothese geeignet ist, **dadurch gekennzeichnet, dass** die Zusammenstellung umfasst:
 - ein femorales Räumwerkzeug (10), das zur Platzierung in einem Knochenhohlraum bestimmt ist, um den Knochenhohlraum (C) zur Implantation einer Prothese (S) vorzubereiten, wobei das femorale Räumwerkzeug (10) ein oberes Ende (12) und eine laterale Seite (L) umfasst, auf der sich eine laterale Ausnehmung (13) vom oberen Ende aus nach unten erstreckt, wobei die Ausnehmung geformt ist, um den Knochen des großen Trochanters zu vermeiden;
 - eine Führung (200), die an dem femoralen Räumwerkzeug (10) befestigt und geformt ist, um ein zweites Knochenschneidinstrument (208) aufzunehmen; und
 - ein in der Führung (200) getragenes zweites Knochenschneidinstrument (208), wobei das zweite Knochenschneidinstrument (208) angepasst ist, um in die laterale Ausnehmung (13) einzutreten, um nach einer Platzierung des femoralen Räumwerkzeugs (10) innerhalb des Hohlraums (C) und vor der Implantation der Prothese innerhalb des vorbereiteten Knochenhohlraums (C) zusätzliches Knochenmaterial von der lateralen Seite des Hohlraums (C) zu entfernen.
2. Bearbeitungszusammenstellung nach Anspruch 1, die einen an dem femoralen Räumwerkzeug (10) befestigten Montageblock (101) einschließt.
3. Bearbeitungszusammenstellung nach Anspruch 2, bei welcher die Führung (200) einen Körper (201) mit einer äußeren Oberfläche (201A) und einem durchgehenden inneren Durchlass (203) umfasst, um das zweite Knochenschneidinstrument (208) zu beherbergen, sowie einen Führungsarm (202), der eine Einheit mit der äußeren Ober-

fläche des Körpers (201) bildet und an einem Montageblock (101) befestigt ist.

4. Bearbeitungszusammenstellung nach Anspruch 3, weiter einschließend eine Einrichtung zur Befestigung der Führung am Montageblock (101), wobei die Befestigungseinrichtung eine innerhalb des Montageblocks (101) enthaltene und durchgehende innere quer verlaufende Kammer (205) einschließt, wobei die Kammer für einen verschiebbaren Eingriff des Führungsarms (202) darin geformt ist.

5. Bearbeitungszusammenstellung nach Anspruch 3 oder Anspruch 4, bei welcher die Einrichtung zur Befestigung der Führung am Montageblock weiter eine Arretierschraube (206) einschließt, die einen Kopf (206a) und einen Unterkörper (206b) aufweist, der in eine auf dem oberen Ende (102) des Blocks angeordnete erste komplementäre Längsbohrung (207) eingreift, wobei die Bohrung mit der quer verlaufenden Kammer (205) in Verbindung steht; wodurch, wenn die Arretierschraube in einer Richtung gedreht wird, der Unterkörper der Schraube einen Kontakt mit dem Führungsarm erzielt, um eine Verschiebewegung des Arms in der Kammer zu verhindern, und wenn die Schraube in entgegengesetzter Richtung gedreht wird, der Unterkörper der Schraube zurückgezogen wird, um den Arm freizugeben, wodurch eine verschiebbare Bewegung des Führungsarms innerhalb der quer verlaufenden Kammer ermöglicht wird.

6. Bearbeitungszusammenstellung nach Anspruch 4 oder Anspruch 5, bei welcher der Führungsarm (202) und die quer verlaufende Kammer (205) geformt sind, um eine Drehbewegung des Führungsarms um eine in der Kammer definierte quer verlaufende Achse (210) zu verhindern.

7. Bearbeitungszusammenstellung nach Anspruch 5 oder Anspruch 6, bei der die Führung weiter eine Einrichtung einschließt, um die Führung an mehreren Positionen in Bezug zum Montageblock einzustellen, wobei die Einstell-einrichtung eine auf dem Führungsarm angeordnete Vertiefung (204) und einen federbelasteten Kolben (300) einschließt, der in eine zweite komplementäre Bohrung (302) eingreift, die parallel zur Arretierschraube (206) und senkrecht zur quer verlaufenden Kammer (205) ist, wobei der Kolben eine in die Kammer ragende untere Spitze (301) aufweist:

wodurch, wenn die Vertiefung unterhalb des Kolbens angeordnet ist, die untere Spitze in der Vertiefung in Eingriff gebracht wird.

8. Bearbeitungszusammenstellung nach ein der vorangehenden Ansprüche 2 bis 7, einschließend Einrichtungen zur Befestigung des femoralen Räumwerkzeugs (10) am Montageblock (101), wobei die Befestigungseinrichtungen einschließen:

- (a) eine erste Bohrung (400), die geformt ist, um einen auf dem oberen Ende (12) des femoralen Räumwerkzeugs (10) angeordneten Vorsprung (18) aufzunehmen; und
- (b) eine Verriegelungsstifanordnung, umfassend einen federbelasteten Stift (401), der in eine erste komplementäre quer verlaufende Kammer (402) eingreift, die oberhalb der ersten Bohrung (400) angeordnet ist, einen Verriegelungsstift (403), der in eine zweite komplementäre quer verlaufende Kammer (404) eingreift, die zu der ersten quer verlaufenden Kammer parallel und zwischen der ersten Kammer und der ersten Bohrung angeordnet ist, wobei die zweite quer verlaufende Kammer mit der ersten Bohrung in Verbindung steht; sowie eine Einrichtung zum Verbinden des Verriegelungsstifts mit dem federbelasteten Stift;

wodurch, wenn der federbelastete Stift betätigt wird, der Verriegelungsstift aus der zweiten quer verlaufenden Kammer ausgerückt wird, um einen Eintritt des Vorsprungs in die erste Bohrung zuzulassen, und wodurch bei einer nachfolgenden Freigabe des federbelasteten Stifts der Verriegelungsstift in der ersten Bohrung in Eingriff gebracht wird, um den Vorsprung des femoralen Räumwerkzeugs (10) darin zu verriegeln.

9. Bearbeitungszusammenstellung nach Anspruch 8, bei welcher der Verriegelungsstift (403) ein verjüngtes Ende aufweist.

10. Bearbeitungszusammenstellung nach Anspruch 8 oder Anspruch 9, bei welcher der Vorsprung (8) eine Raste (19) einschließt, die geformt ist, um den Verriegelungsstift (403) zur starren Befestigung des femoralen Räumwerkzeugs (10) in der ersten Bohrung (400) aufzunehmen.

11. Bearbeitungszusammenstellung nach einem der vorangehenden Ansprüche 8, 9 oder 10, bei welcher das untere Ende (103) des Montageblocks (101) ein Federelement (406) aufweist, das sich unterhalb der ersten Bohrung

(400) nach unten erstreckt und geformt ist, um in eine komplementäre Nut (20) einzugreifen, die benachbart zum Vorsprung auf dem oberen Ende (12) des femoralen Räumwerkzeugs (10) angeordnet ist; wodurch, wenn der Vorsprung starr mit der ersten Bohrung des Montageblocks in Eingriff gebracht ist, das Feder-
 5 element in die Nut eingreift, um eine Drehbewegung des Montageblocks um die Längsachse (X) des femoralen Räumwerkzeugs (10) auszuschließen.

12. Bearbeitungszusammenstellung nach Anspruch 1, bei welcher das femorale Räumwerkzeug (10) umfasst: eine Längsachse (X), eine anteriore (A), eine posteriore (P), eine mediale (M) und eine laterale (L) Seite, eine Mehrzahl von Schneidzähnen (17), die auf mindestens einer der Seiten angeordnet sind, einen proximalen Abschnitt, der
 10 die Seiten einschließt und ein oberes Ende (12) und eine Ausnehmung (13) aufweist, welche auf der lateralen Seite des proximalen Abschnitts angeordnet ist und sich vom oberen Ende aus nach unten erstreckt, wobei die Ausnehmung geformt ist, um nach einer Implantation des Räumwerkzeug innerhalb des Hohlraums den Knochen des großen Trochanters zu vermeiden.

13. Bearbeitungszusammenstellung nach Anspruch 12, bei welcher sich die Ausnehmung (13) von der posterioren (P) Seite bis zu der anterioren (A) Seite erstreckt.

14. Bearbeitungszusammenstellung nach Anspruch 13, bei welcher die Ausnehmung (13) einen Rückenteil (14) und einen Fußteil (15) einschließt.

15. Bearbeitungszusammenstellung nach Anspruch 14, bei welcher der Fußteil eine Konkavität (15) umfasst, die eine distale Kante (16) aufweist.

16. Bearbeitungszusammenstellung nach Anspruch 15, bei welcher die Ausnehmung weiter eine Abschrägung (15b) einschließt, die sich von der distalen Kante (16) der Konkavität (15a) aus nach unten erstreckt.

Revendications

1. Ensemble d'usage approprié pour être utilisé pour préparer une cavité osseuse pour l'implantation ultérieure d'une prothèse, **caractérisé en ce que** ledit ensemble comprend :

une broche fémorale (10) conçue pour être disposée à l'intérieur d'une cavité osseuse pour préparer ladite cavité osseuse (C) pour l'implantation d'une prothèse (S), ladite broche fémorale (10) comprenant une extré-
 35 mité supérieure (12), et une face latérale (L) sur laquelle se trouve une cavité latérale (13) s'étendant vers le bas à partir de ladite extrémité supérieure, ladite cavité étant configurée pour éviter l'os du grand trochanter ; un guide (200) fixé à ladite broche fémorale (10) et configuré pour recevoir un deuxième instrument de coupe d'os (208) ; et

un deuxième instrument de coupe d'os (208) porté à l'intérieur dudit guide (200), ledit deuxième instrument de coupe d'os (208) étant adapté pour entrer dans ladite cavité latérale (13) pour retirer un matériau osseux
 40 additionnel à partir du côté latéral de la cavité (C) après la disposition de ladite broche fémorale (10) à l'intérieur de ladite cavité (C) et avant l'implantation de ladite prothèse à l'intérieur de ladite cavité osseuse préparée (C).

2. Ensemble d'usage selon la revendication 1, qui comprend un bloc de montage (101) fixé à ladite broche fémorale (10).

3. Ensemble d'usage selon la revendication 2, dans lequel ledit guide (200) comprend un corps (201) comportant une surface extérieure (201A) et un passage intérieur (203) communiquant à travers celui-ci pour recevoir ledit deuxième instrument de coupe d'os (208), et un bras de guidage (202) intégré à ladite surface extérieure dudit
 50 corps (201) et fixé à un bloc de montage (101).

4. Ensemble d'usage selon la revendication 3, comprenant de plus des moyens pour fixer ledit guide audit bloc de montage (101), lesdits moyens de fixation comprenant une chambre transversale intérieure (205) contenue à l'intérieur dudit bloc de montage (101) et communiquant à travers celui-ci, dans lequel ladite chambre est confi-
 55 gurée pour une prise de coulissement dudit bras de guidage (202) à l'intérieur de celle-ci.

5. Ensemble d'usage selon la revendication 3 ou la revendication 4, dans lequel lesdits moyens pour fixer ledit guide audit bloc de montage comprennent de plus une vis de verrouillage (206) comportant une tête (206a) et un

corps inférieur (206b) venant en prise à l'intérieur d'un premier perçage longitudinal complémentaire (207) positionné sur l'extrémité supérieure (102) du bloc, ledit perçage étant en communication avec ladite chambre transversale (205) ;

grâce à quoi, lorsque ladite vis de verrouillage est tournée dans une direction, le corps inférieur de la vis rentre en contact avec ledit bras de guidage afin d'empêcher un mouvement de coulissement dudit bras à l'intérieur de la chambre, et, lorsque ladite vis est tournée dans une direction opposée, ledit corps inférieur de la vis est rétracté de façon à libérer ledit bras, de façon à permettre par conséquent un mouvement de coulissement du bras de guidage à l'intérieur de la chambre transversale.

6. Ensemble d'usinage selon la revendication 4 ou la revendication 5, dans lequel ledit bras de guidage (202) et ladite chambre transversale (205) sont configurés pour empêcher un mouvement de rotation dudit bras de guidage autour d'un axe transversal (210) défini à l'intérieur de ladite chambre.

7. Ensemble d'usinage selon la revendication 5 ou la revendication 6, dans lequel ledit guide comprend de plus des moyens pour ajuster le guide en des positions multiples par rapport audit bloc de montage, lesdits moyens d'ajustage comprenant une indentation (204) positionnée sur ledit bras de guidage et un plongeur sollicité par un ressort (300) venant en prise dans un deuxième perçage complémentaire (302) parallèle à ladite vis de verrouillage (206) et perpendiculaire à ladite chambre transversale (205), ledit plongeur comportant une pointe inférieure (301) faisant saillie à l'intérieur de ladite chambre ;

grâce à quoi, lorsque ladite indentation est positionnée en dessous dudit plongeur, la pointe inférieure vient en prise à l'intérieur de ladite indentation.

8. Ensemble d'usinage selon l'une quelconque des revendications 2 à 7 qui précèdent, comprenant des moyens pour fixer ladite broche fémorale (10) audit bloc de montage (101), lesdits moyens de fixation comprenant :

(a) un premier perçage (400) configuré pour recevoir une protubérance (18) positionnée sur ladite extrémité supérieure (12) de ladite broche fémorale (10) ; et

(b) un ensemble de broches de verrouillage comprenant une broche sollicitée par un ressort (401) venant en prise à l'intérieur d'une première chambre transversale complémentaire (402) positionnée au-dessus dudit premier perçage (400), une broche de verrouillage (403) venant en prise à l'intérieur d'une deuxième chambre transversale complémentaire (404) parallèle à ladite première chambre transversale et positionnée entre ladite première chambre et ledit premier perçage, ladite deuxième chambre transversale étant en communication avec ledit premier perçage ; et des moyens pour raccorder ladite broche de verrouillage à ladite broche sollicitée par un ressort ;

grâce à quoi, lorsque ladite broche sollicitée par un ressort est actionnée, ladite broche de verrouillage quitte sa prise avec ladite deuxième chambre transversale de façon à permettre l'entrée de ladite protubérance à l'intérieur dudit premier perçage, et grâce à quoi, lors de la libération ultérieure de ladite broche sollicitée par un ressort, ladite broche de verrouillage vient en prise à l'intérieur dudit premier perçage de façon à verrouiller ladite protubérance de ladite broche fémorale (10) à l'intérieur de celui-ci.

9. Ensemble d'usinage selon la revendication 8, dans lequel ladite broche de verrouillage (403) a une extrémité effilée.

10. Ensemble d'usinage selon la revendication 8 ou la revendication 9, dans lequel ladite protubérance (18) comprend une encoche (19) configurée pour recevoir ladite broche de verrouillage (403) pour une fixation rigide de ladite broche fémorale (10) à l'intérieur dudit premier perçage (400).

11. Ensemble d'usinage selon l'une quelconque des revendications 8, 9 ou 10 qui précèdent, dans lequel l'extrémité inférieure (103) dudit bloc de montage (101) comporte un élément de clavette (406) s'étendant vers le bas en dessous dudit premier perçage (400), et configuré de façon à venir en prise avec une rainure complémentaire (20) fixée sur ladite extrémité supérieure (12) de ladite broche fémorale (10) au voisinage de ladite protubérance ; grâce à quoi, lorsque ladite protubérance vient en prise de façon rigide avec ledit premier perçage dudit bloc de montage, ledit élément de clavette vient en prise à l'intérieur de ladite rainure de façon à empêcher un mouvement de rotation dudit bloc de montage autour de l'axe longitudinal (X) de ladite broche fémorale (10).

12. Ensemble d'usinage selon la revendication 1, dans lequel ladite broche fémorale (10) comprend un axe longitudinal (X) ; des faces antérieure (A), postérieure (B), médiane (M) et latérale (L) ; une pluralité de dents de coupe (17) positionnées sur au moins l'une desdites faces ; un segment proximal comprenant lesdites faces et comportant

une extrémité supérieure (12) et une cavité (13) positionnée sur ladite face latérale dudit segment proximal et s'étendant vers le bas à partir de ladite extrémité supérieure, ladite cavité étant configurée de façon à éviter le grand os trochantérien lors de l'implantation de ladite broche à l'intérieur de ladite cavité.

- 5 **13.** Ensemble d'usinage selon la revendication 12, dans lequel ladite cavité (13) s'étend de ladite face postérieure (P) à ladite face antérieure (A).
14. Ensemble d'usinage selon la revendication 13, dans lequel ladite cavité (13) comprend une partie arrière (14) et une partie de base (15).
- 10 **15.** Ensemble d'usinage selon la revendication 14, dans lequel ladite partie de base comprend une concavité (15a) comportant un bord distal (16).
- 15 **16.** Ensemble d'usinage selon la revendication 15, dans lequel ladite cavité comprend de plus un chanfrein (15b) s'étendant vers le bas à partir dudit bord distal (16) de ladite concavité (15a).

20

25

30



35

40

45

50

55






FIG. 3




FIG. 3A







FIG. 3B






FIG. 6A




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18

FIG.19








FIG.20








FIG. 25A




FIG. 25B




FIG. 25C